



SPECIFICATIONS

	2012	2026	2041	2044 / 2054	2056	2066* / 2076	2086	2700V	2109
DIMENSIONS									
A. Overall Operating Height - Fully Raised (mm)	124.7" (3167)	139.6" (3546)	141.1" (3584)	143.5"/146.5" (3645/3721)	160" (4064)	162" (4115)	168.3" (4275)	169.8" (4313)	187.8" (4770)
B. Height to Hinge Pin - Fully Raised (mm)	96" (2438)	108.1" (2746)	110" (2794)	112"/116" (2845/2946)	120.7" (3066)	123" (3124)	123" (3124)	130.3" (3310)	142" (3607)
C. Overall Height to Top of ROPS (mm)	74.7" (1897)	70.3" (1786)	71.9" (1826)	77.7" (1973)	78.0" (1981)	81" (2057)	81" (3057)	80.5" (2045)	81" (2057)
D. Ground Clearance to Chassis (mm)	5.9" (150)	6" (152)	8.3" (211)	7.5"/7.8" (191/197)	7.5" (191)	8.0" (203)	8.0" (203)	8.0" (203)	9.1" (231)
E. Overall Length with Bucket (mm)	101.4" (2576)	114" (2896)	116.2" (2952)	123.5"/125.5" (3137/3188)	126.3" (3208)	131" (3327)	140.3" (3563)	149.2" (3790)	161" (4089)
F. Overall Length without Bucket (mm)	75" (1905)	88.9" (2258)	91.1" (2314)	95"/97" (2413/2448)	94.2" (2393)	99.5" (2527)	105.8" (2687)	115" (2921)	122" (3099)
G. Wheelbase (mm)	30.5" (77)	34.5" (876)	36.7" (932)	36.7"/38.5" (932/978)	42" (1067)	42.5" (1080)	48.4" (1229)	49.8" (1265)	55" (1397)
H. Dump Reach at Full Height (mm)	14.8" (376)	22.8" (579)	22.6" (574)	25.7"/24" (654/610)	23.1" (587)	32" (813)	35.2" (894)	35" (864)	38.2" (970)
I. Rollback at Ground	23.4°	29°	29°	28°	23°	28°	28°	28°	28.5°
J. Dump Angle	46°	42°	42°	32°/34°	43°	37°	37°	41°	38°
K. Overall Width (mm)	35.8" (909)	48.4" (1229)	55" (1397)	59"/60.7" (1499/1542)	62"/59.7" (1575/1516) ^E	69" (1753)	69" (1753)	69.5" (1661)	81" (2057)
L. Bucket Width (mm)	36" (914)	55" (1397)	55" (1397)	61.5" (1562)	60" (1524)	70" (1778)	74" (1880)	70" (1778)	84" (2134)
M. Clearance Circle - Rear (mm)	43.2" (1097)	54.1" (1374)	58.4" (1484)	50.5"/59.3" (1283/1506)	58" (1473)	66" (1679)	69" (1753)	65.5" (1664)	8035" (2045)
N. Clearance Circle - Front w/o Bucket (mm)	32.8" (833)	44.1" (1120)	43.4" (1102)	39.3"/45.8" (997/1162)	45" (1143)	50.5" (1283)	54" (1372)	74.6" (1895)	60.6" (1539)
O. Clearance Circle - Front w/ Bucket (mm)	58" (1473)	69.4" (1763)	69.2" (1758)	73"/74.5" (1854/1892)	79" (2006)	82" (2083)	90" (2299)	93" (2362)	102" (2583)
P. Seat to Ground Height (mm)	34.6" (879)	32.6" (828)	33.6" (853)	34.6"/34.8" (879/884)	39.7" (1008)	42" (1067)	42" (1067)	40.2" (1021)	41" (1041)
Q. Rollback at Full Height	61°	99°	99°	100°	91°	84°	84°	94°	85°
R. Dump Height (mm)	72.3" (1836)	84.5" (2146)	86.5" (2197)	88.2"/92" (2242/2337)	90" (2286)	93.5" (2375)	92.7" (2354)	99" (2515)	107" (2718)
S. Departure Angle	30°	26°	29°	24°/26°	25°	26°	26°	27°	21°
Standard Tire Size	5.70x12	27x8.5x15 HD	10.00x16.5 HD	10.00x16.5 HD	10.00x16.5 HD	12.00x16.5 HD	12.00x16.5 HD	12.00x16.5 HD	14x17.5 HD
ENGINE									
Make	Yanmar	Yanmar	Yanmar	Yanmar	Deutz	Yanmar	Yanmar	Yanmar	Cummins
Model	3TNV82 - Tier III	3TNV88 - Tier III	4TNV88 - Tier III	4TNV88 - Tier III	TD2009 - Tier III	4TNV98*/4TNV98T - Tier III	4TNV98T - Tier III	4TNV98T - Tier III	B4.5T-99C - Tier II
Net Power (kW) @ rpm	24 hp (17.9) @ 2400	35 hp (26) @ 2600	46 hp (34) @ 2600	47 hp (35) @ 3000	62 hp (46) @ 2500	68/84 hp (51/62.6) @ 2500	84 hp (62.6) @ 2500	84 hp (62.6) @ 2500	99 hp (73.8) @ 2200
Displacement (L)	81 cu.in. (1.33)	100 cu.in. (1.64)	134 cu.in. (2.2)	133.6 cu.in. (2.19)	140 cu. in. (2.3)	202 cu.in. (3.3)	202 cu.in. (3.3)	202 cu. in. (3.3)	275 cu.in. (4.5)
HYDRAULIC SYSTEM									
Auxiliary Hydraulics - Standard (L/min)	9.1 gpm (34)	14.5 gpm (55)	16.5 gpm (62.5)	18 gpm (68.1)	19 gpm (72)	21.8 gpm (82.3)	21.8 gpm (82.3)	21.8 gpm (82.5)	29 gpm (110)
High-Flow (L/min)	N/A	N/A	N/A	N/A / 28 gpm (106)	30 gpm (114)	36.9 gpm (139.6)	36.9 gpm (139.6)	36.9 gpm (139.7)	41 gpm (155.2)
Filtration	4 micron	4 micron	4 micron	7 micron	4 micron	4 micron	4 micron	4 micron	4 micron
Reservoir Capacity (L)	7.15 gal. (27.1)	8 gal. (30.3)	8 gal. (30.3)	11.5 gal. (43.5)	12 gal. (45)	16 gal. (60)	16 gal. (60)	11 gal. (41.6)	15 gal. (56.8)
ELECTRICAL SYSTEM									
Battery	12-volt (650 CCA)	12-volt (675 CCA)	12-volt (675 CCA)	12-volt (700/950 CCA)	12-volt (950 CCA)	12-volt (950 CCA)	12-volt (950 CCA)	12-volt (950 CCA)	12-volt (1500 CCA)
Starter (kW)	12-volt (2.0)	12-volt (2.0)	12-volt (3.0)	12-volt (3.0)	12-volt (2.0)	12-volt (3.0)	12-volt (3.0)	12-volt (3.0)	12-volt (4.8)
Alternator	40-amp	40-amp	40-amp	40-amp	80-amp	90-amp	90-amp	90-amp	95-amp
CAPACITIES / WEIGHTS									
Rated Operating Capacity ^B (kg)	850 lbs. (385)	1050 lbs. (476)	1350 lbs. (612)	1450/1650 lbs. (658/748)	1900 lbs. (862)	2000/2200 lbs. (907/998)	2600 lbs. (1179)	2700 lbs. (1225)	3850 lbs. (1747)
With Opt. Counterweight ^B (kg)	N/A	1175 lbs. (533)	1475 lbs. (669)	1550/1750 lbs. (703/794)	2050 lbs. (930)	2300/2500 lbs. (1043/1134)	2900 lbs. (1315)	3000 (1361)	N/A
Tipping Load ^B (kg)	1709 lbs. (775)	2100 lbs. (952)	2700 lbs. (1225)	2900/3300 lbs. (1315/1497)	3800 lbs. (1724)	4400 lbs. (1995)	5200 lbs. (2358)	5400 (2449)	7700 lbs. (3493)
Fuel Tank (L)	7.7 gal. (29)	10.3 gal. (38.9)	12.4 gal. (47)	14.3 gal. (54.1)	16 gal. (60)	19 gal. (71.9)	24 gal. (91)	22 gal. (83.3)	30.5 gal. (115)
Travel Speed - Maximum (km/h)	5.5 mph (8.9)	5.9 mph (9.5)	6.4 mph (10.3)	6.6/6.8 mph (11.3/10.9)	12.4 mph (20) ^D	12.3 mph (19.8) ^D	12.3 mph (19.8) ^D	11.9 mph (19.2) ^D	12.5 mph (20) ^D
Operating Weight ^C - Appx. (kg)	2980 lbs. (1352)	4000 lbs. (1814)	4600 lbs. (2087)	5623/6080 lbs. (2551/2758)	6800 lbs. (3084)	7460/7480 lbs. (3384/3393)	7900 lbs. (3583)	8000 lbs. (3629)	10,520 lbs. (4772)

REFERENCE DIAGRAMMS

2700V / 2109 REFERENCE DIAGRAMMS



MUSTANG
West Bend, WI 53095 USA
PH: 262.334.9461
FX: 262.334.7517
mustangmfg.com

* 2066 not available in Europe.

B - Per SAE J818, J732 and ISO 14397.

C - Weight of base unit with std. equipment, std. tires, std. bucket, 175 lb. (79 kg) operator, and full fuel tank.

D - With optional 2-speed.

E - With narrow off-set wheel option

Mustang reserves the right to make changes in specifications at any time without notice or obligation.

For more information on Mustang equipment, call our literature hotline at **800-628-0491** or visit our website: **mustangmfg.com**



Mixed Sources
Product group from well-managed forests, controlled sources and recycled wood or fiber
www.fsc.org Cert no. SGS-COC-005150
© 1996 Forest Stewardship Council

